



www.csfima.it


Manufacturer of accessories and springs for roller shutters. Steel and aluminum coils, strips and sheets.



*"Quality is never an accident;
it is always the result
of intelligent effort."*

John Ruskin

c.s.fima SRL Quality Designers





INNOVATIVE SOLUTIONS: FIMASILENCE, NAYSTEEL AND FIMASPRING

COILS, STRIPS, SHEET METAL AND MICRO PERFORATED METAL

SPRING BOXES

ACCESSORIES FOR ROLLER SHUTTERS


SAFETY DEVICES

GASKETS, PROFILES AND SLIDING BLOCKS

ACCESSORIES FOR VERTICAL SHUTTERS

LOCKS

ACCESSORIES FOR EXTENDABLE GATES



Made in Italy

The “Made in Italy” brand represents the know-how of those who distinguish themselves for creativity, design and quality.

We are proud to be promoters of this brand.

Know-how and quality

Our years of experience and knowledge along with the expertise of our collaborators allows us to look after every phase of our production, from concept to development and realization. This is because “a high-quality product is one that fully meets the needs of those who use it.”



PATENTED

Its silence means your serenity.


It seems like a dream but FimaSilence® actually exists! The first shutter in the world designed to reduce noise and vibrations up to 80%.



FimaSilence® was designed to give you the peace and serenity to live in your home without producing noise pollution that could disturb the tranquillity and sleep of your neighbours.



What makes it silent



Two steel strips are mated together using a double-sided adhesive polymer that dampens the sound. A much better system than traditional rolling shutters with PVC gaskets.

Painting

Resistant to processes of painting, in the oven, up to 200° C.



Why choose FimaSilence



UP TO 20db QUIETER

This highly innovative patented material reduces noise and vibrations up to 80% while maintaining a traditional aesthetic.



RESISTANT TO HIGH TEMPERATURES

Two steel strips are mated together using a double-sided adhesive polymer. It's also resistant to painting processes, in the oven, up to 200° C.



PATENTED TECHNOLOGY

The innovative system, composed of a polymer enclosed between two sheets of steel, makes FimaSilence the only product of its kind in the world. Unlike standard rolling shutters that rely on the use of gaskets, FimaSilence maintains silence over time.



VERSATILE

You have the opportunity to make a new rolling shutter or to upgrade the old ones by replacing only the curtain.



comparative equivalent sound level tests				
With 220V gear motor Results				
L _{Aeq}	Standard Curtain		FimaSilenceCurtain	
	CH1**	CH3**	CH1**	CH3**
Rolling shutter opening	84,3 dB	84,3 dB	73,3 dB	69,7 dB
Rolling shutter closing	81,0 dB	80,8 dB	70,4 dB	67,9 dB

(**) CH1 = microphones on the source room side.
CH3 = microphones on the receiving room side.

With 24V gear motor Results				
L _{Aeq}	Standard Curtain		FimaSilenceCurtain	
	CH1**	CH3**	CH1**	CH3**
Rolling shutter opening	77,9 dB	78,2 dB	59,5 dB	56,9 dB
Rolling shutter closing	79,1 dB	78,7 dB	53,1 dB	52,4 dB

(**) CH1 = microphones on the source room side.
CH3 = microphones on the receiving room side.





The Naysteel® spring box substitutes the classic steel or nylon ball system with a single self-lubricating nylon component, reducing the risk of breakage from wear and tear or continuous loads.

The certified materials' quality and a highly automated production guarantee high quality and consistent standards over time.





Certified spring box with nylon bushing


Why choose Naysteel:

- Certified for 10,000 cycles
- Tested in our laboratory for over 150,000 cycles
- Silent
- Guaranteed performance even with anomalous tube bending
- Possibility to reduce the spring box holder for 60 mm tubes to 48 or 42 mm tubes



The Naysteel® spring box, having at its core a single self-lubricating nylon block, is capable of withstanding both constant weight of the shutter as well as continuous movement on the tubing, all without damaging or cutting it.

An original product, customizable and certified. 100% Made in Italy.





FimaSpring® is the only shutter spring of its kind.

FimaSpring is the shutter spring patented by CS Fima. Its low carbon level and a dedicated thermal treatment give the FimaSpring a reliable and long-lasting performance making it stand out from others on the market.

Thanks to our commitment to excellence and numerous studies and tests performed throughout the years, today FimaSpring has reached high quality and performance standards.



PATENTED





Certified rolling shutter spring

Why choose FimaSpring:

- Certified for 15,000 cycles by the Giordano Institute S.p.A.
- Tested in our laboratory for 30,000 cycles
- Force Capacity for all models and dimensions are lab tested to guarantee maximum precision balance
- Consistent and repeatable mechanical uniformity for every order
- Resistant to thermal excursion and low temperatures
- Strips with rounded edges
- Perfectly flat surface

The "white" spring with red strap.

It's easy to recognize the FimaSpring compared to other springs on the market. The impact of the bright and unmistakable red strap covering the shutter spring is one of the main visual differences that gives way to even more technical differences.

Its low carbon level and a dedicated thermal treatment give FimaSpring the ability to work in a range between +100°C to -40°C.

An original, customizable and certified product. 100% Made in Italy.






Certified roller shutter spring

Availability and force capacity of the FimaSpring.


For every FimaSpring spring size shown in our catalogue the force capacity has been tested in order to guarantee maximum precision of the shutter system's balance.



This commitment to excellence ensures that every spring provided offers reliable performance over time, meeting your maximum precision needs.



Code	W	T	Force capacity in Kg Ø 200 mm	Force capacity in Kg Ø 220 mm	Force capacity in Kg Ø 240 mm	Force capacity in Kg Ø 280 mm	Weight Kg/m	Roll Kg
70D 3511	35	1,1	13	12,1	11,2	9,9	0,302	80
70D 4011	40	1,1	16	14,9	13,8	12,2	0,345	80
70D 4012	40	1,2	18	16,7	15,5	13,7	0,377	80
70D 4013	40	1,3	22	20,5	18,9	16,7	0,408	80
70D 4014	40	1,4	25	23,3	21,5	19,0	0,440	80
70D 4511	45	1,1	18	16,7	15,5	13,7	0,389	80
70D 4512	45	1,2	20	18,6	17,2	15,2	0,424	80
70D 4513	45	1,3	23	21,4	19,8	17,5	0,459	80
70D 4514	45	1,4	26	24,2	22,4	19,8	0,495	80
70D 5011	50	1,1	20	18,6	17,2	15,2	0,432	80
70D 5012	50	1,2	22	20,5	18,9	16,7	0,471	80
70D 5013	50	1,3	27	25,1	23,2	20,5	0,510	80
70D 5014	50	1,4	30	27,9	25,8	22,8	0,550	80
70D 5511	55	1,1	22	20,5	18,9	16,7	0,475	80
70D 5512	55	1,2	25	23,3	21,5	19,0	0,518	80
70D 5513	55	1,3	30	27,9	25,8	22,8	0,561	80
70D 5514	55	1,4	33	30,7	28,4	25,1	0,604	80
70D 6011	60	1,1	25	23,3	21,5	19,0	0,518	80
70D 6012	60	1,2	26	24,2	22,4	19,8	0,565	80
70D 6013	60	1,3	33	30,7	28,4	25,1	0,612	80
70D 6014	60	1,4	36	33,5	31,0	27,4	0,659	80
70D 7012	70	1,2	31	28,8	26,7	23,6	0,659	80
70D 7013	70	1,3	43	40,0	37,0	32,7	0,714	80
70D 7014	70	1,4	45	41,9	38,7	34,2	0,769	80
70D 8014	80	1,4	54	50,2	46,4	41,0	0,879	80



* FimaSpring and tempered spring comparison

◆ C67S
▲ FIMA'SPRING



Roller shutter C67S tempered spring

Availability and force capacity of the C67S tempered spring

Our well-stocked warehouse allows us to have all available dimensions and offer quick delivery times.



The C67S tempered strips have rounded edges.

Force capacity for the C67S tempered spring

Code	W	T	Force capacity in Kg Ø 200 mm	Weight Kg/m	Roll Kg
70M 4010	40	1,0	14	0,314	80
70M 4011	40	1,1	15	0,345	80
70M 4012	40	1,2	16	0,377	80
70M 4013	40	1,3	17	0,408	80
70M 4014	40	1,4	20	0,440	80
70M 4510	45	1,0	16	0,353	80
70M 4511	45	1,1	17	0,389	80
70M 4512	45	1,2	19	0,424	80
70M 4513	45	1,3	22	0,459	80
70M 4514	45	1,4	25	0,495	80
70M 5010	50	1,0	18	0,393	80
70M 5011	50	1,1	20	0,432	80
70M 5012	50	1,2	23	0,471	80
70M 5013	50	1,3	26	0,510	80
70M 5014	50	1,4	29	0,550	80
70M 5510	55	1,0	20	0,432	80
70M 5511	55	1,1	23	0,475	80
70M 5512	55	1,2	27	0,518	80
70M 5513	55	1,3	30	0,561	80
70M 5514	55	1,4	35	0,604	80
70M 6010	60	1,0	23	0,471	80
70M 6011	60	1,1	26	0,518	80
70M 6012	60	1,2	30	0,565	80
70M 6013	60	1,3	35	0,612	80
70M 6014	60	1,4	39	0,659	80
70M 7013	70	1,3	44	0,714	80
70M 7014	70	1,4	50	0,769	80
70M 8014	80	1,4	63	0,879	80







nastri

- Cutting steel coils, strips and sheets
- Many years of experience in the field
- High quality standards
- Wide range of products



Coils, strips and sheets.

- **Pickled**
- **Cold-rolled**
- **Chromables**
- **Tempered and temperable**
- **Galvanized and otherwise coated**
- **Thicknesses from 0.20mm to 3.00mm**
- **Widths from 4.00mm to 1700mm**





nastri 

- Ability to adapt to any requirement
- Supplies of small quantities and containers
- Well-stocked warehouse
- Fast shipping






Coils, strips and sheets.

■ **Technical advice for the right choice of materials to be used.**

■ **Laboratory to carry out mechanical tests**

■ **Materials characterization**

■ **Compliance with required specifications**





Microperforated steel strips

Microperforated steel strips are available in:


- Galvanized steel
- Pre-painted steel
- Stainless steel Aisi 304 and 316
- Super Galva steel Anti-corrosion
- Aluminum



**THE PERFECT
SOLUTION
TO GET NOTICED**



HOLE \varnothing 2,50MM - PITCH 3,50MM



90NM

In galvanized steel


500
KG

90NMZM

«Super Galva» high corrosion resistance

500
KG

HOLE \varnothing 4,00MM - PITCH 6,00MM



904NM

In galvanized steel

500
KG

904NMZM

«Super Galva» high corrosion resistance

500
KG

904NMAL

In aluminium

500
KG

904NMINOX

In stainless steel aisi 304 - 316 - 444

500
KG

904NMPR

In pre-painted steel

500
KG



It's good for airing the shop, or to display your products even when you're shut, and the measurements are customized.



Pre-painted imitation wood with grain in relief

Pre-painted imitation wood "touch effect" tape

- Resistant to UV fluorescent light (sun)
- No colour variation over time
- Excellent paint adhesion
- Coating up to 50 microns
- High resistance to corrosion
- Embossed wood grain
- Easy to profile
- Supply of strips also in small quantities
- Always available in stock

**Other colors available
with and without
"TOUCH EFFECT"**



**WOOD
CLEAR**



**WOOD
DARK**



**TOUCH
EFFECT**



The effect is amazing!
My garage has completely
changed its look.
Recommended!







It looks like parquet,
difficult to tell the
difference between it
and real wood.
It's incredible that it's steel



My shopfront has
become very stylish.
Being situated on the sea
front, it's a fantastic
solution.



"SUPER GALVA" tape

-  ***Prevents corrosion***
-  ***High level of protection compared to standard galvanized strips***
-  ***Self-healing protection on cut and perforated edges***
-  ***Suitable for the most aggressive environments such as maritime environments***

Salt spray testing



Self-healing protection on cut edges. Outdoor exposure in different periods of time.


Marine category C5-M (the most severe)



Standard galvanized
40% red rust
60% white rust



SUPER GALVA
10% red rust
90% white rust



**Ideal for
Microperforated
steel strips**



★★★★★
It's incredible, after one year it is still in perfect state of preservation and my store is on the seafont.



★★★★★
Ideal for those who have always had problems with rust like my garage



Spring boxes

Our high level quality materials and automated processes guarantee high and constant level quality over time, with a wide range of solutions.

Spring boxes





Naysteel Spring Box

Ø 240MM - TUBE Ø 76MM



SNA2407640Z

Spring's width 40 mm

70
PCS

SNA2407650Z

Spring's width 50 mm

70
PCS

SNA2407660Z

Spring's width 60 mm

70
PCS

SNA2407670Z

Spring's width 70 mm

50
PCS

SNA2407680Z

Spring's width 80 mm

50
PCS

Naysteel Spring Box

Ø 220MM - TUBE Ø 60MM



SNA2206040Z

Spring's width 40 mm

85
PCS

SNA2206050Z

Spring's width 50 mm

85
PCS

SNA2206060Z

Spring's width 60 mm

85
PCS

SNA2206070Z

Spring's width 70 mm

70
PCS

SNA2206080Z

Spring's width 80 mm

70
PCS

Naysteel Spring Box

Ø 220MM - TUBE Ø 48MM



SNA2204840Z

Spring's width 40 mm

85
PCS

SNA2204850Z

Spring's width 50 mm

85
PCS

SNA2204860Z

Spring's width 60 mm

85
PCS

SNA2204870Z

Spring's width 70 mm

70
PCS

SNA2204880Z

Spring's width 80 mm

70
PCS

Naysteel Spring Box

Ø 200MM - TUBE Ø 60MM



SNA2006040Z

Spring's width 40 mm

100
PCS

SNA2006050Z

Spring's width 50 mm

100
PCS

SNA2006060Z

Spring's width 60 mm

100
PCS

SNA2006070Z

Spring's width 70 mm

70
PCS

SNA2006080Z

Spring's width 80 mm

70
PCS

Naysteel Spring Box

Ø 200MM - TUBE Ø 48MM



SNA2004840Z

Spring's width 40 mm

100
PCS

SNA2004850Z

Spring's width 50 mm

100
PCS

SNA2004860Z

Spring's width 60 mm

100
PCS

SNA2004870Z

Spring's width 70 mm

70
PCS

SNA2004870Z

Spring's width 80 mm

70
PCS

Nylon cover ring for spring boxes



SRA1461

Ø 200 mm

100
PCS

SRA1462

Ø 220 mm

100
PCS

SRA1463

Ø 240 mm

100
PCS

SRA1464

Ø 280 mm

100
PCS

Reducer for

Ø 42MM E Ø 48MM



SNAB42

Naysteel® reducer from Ø 60 mm to Ø 42 mm for Naysteel® spring boxes of Ø 200 mm and 220 mm

SNAB48

Naysteel® reducer from Ø 60 mm to Ø 48 mm for Naysteel® spring boxes of Ø 200 mm and 220 mm

Spring box, Nylon balls

Ø 280MM - TUBE Ø 101MM

SSN28010160

Larghezza molla 60 mm

SSN28010170

Larghezza molla 70 mm

SSN28010180

Larghezza molla 80 mm

Ø 240MM - TUBE Ø 101MM

SSN2406050

Spring width 50 mm

SSN2406060

Spring width 60 mm

SSN2406070

Spring width 70 mm

SSN2406080

Spring width 80 mm

Iron bumpers with "C"



SRA162Z

Iron bumpers with "C" slot to screw

Compatible with **SRA1662 - SRA301Z**

150
PZ

Iron bumpers with "U"



SRA156Z

Iron bumpers with "U" slot to screw

Compatible with **SRA1662 - SRA301Z**

150
PZ

Rubber bumper with interlocking



SRA1662

Rubber bumper with interlocking

compatible with **SRA162Z-SRA156Z**

150
PZ

Nylon handle



SRA158Z

Nylon handle compatible with

SRA160Z - SRA161Z

150
PZ

Galvanized steel handle



SRA159Z

Galvanized steel handle compatible with

SRA160Z - SRA161Z

150
PZ

Fixing plate for handle



SRA160Z

Type "Italy" galvanized steel compatible with

SRA158Z - SRA159Z - SRA301Z

150
PZ

Fixing plate for handle



SRA161Z

Galvanized steel "France" type compatible with

SRA158Z - SRA159Z

150
PZ

Watch the tutorial video



Nylon handle resilience test.

At 144.1 kilograms of applied force with no evidence of damage to the nylon handle.





Kit
Nylon handle +
Iron bumpers with "C" slot



SRA136Z

Includes

60
PZ

SRA158Z - No. 1 nylon handle
SRA160Z - No. 1 fixing plate for handle type "Italy"
SRA162Z - No. 2 Iron bumpers with "C" slot to screw
SRA166Z - No. 2 Rubber bumper with interlocking

Kit
Nylon handle +
Iron bumpers with "U" slot



SRA138Z

Includes

60
PZ

SRA158Z - Nr. 1 nylon handle
SRA160Z - Nr. 1 fixing plate for handle type "Italy"
SRA156Z - Nr. 2 iron bumpers with "U" slot to screw
SRA166Z - Nr. 2 rubber bumpers with interlocking

Kit
Galvanized steel handle +
Iron bumpers with "C" slot



SRA137Z

Includes

60
PZ

SRA159Z - No. 1 galvanized steel handle
SRA160Z - No. fixing plate for handle type "Italy"
SRA162Z - No. 2 Iron bumpers with "C" slot to screw
SRA166Z - No. 2 Rubber bumper with interlocking

Kit
Galvanized steel handle +
Iron bumpers with "U" slot



SRA139Z

Includes


60
PZ

SRA159Z - Nr. 1 galvanized steel handle
SRA160Z - Nr. 1 fixing plate for handle type "Italy"
SRA156Z - Nr. 2 iron bumpers with "U" slot to screw
SRA166Z - Nr. 2 rubber bumpers with interlocking


**SRA162Z +
SRA166Z**




**SRA162Z +
SRA166Z**



**SRA160Z +
SRA158Z**



**SRA156Z +
SRA166Z +
SRA1476**




**SRA160Z +
SRA158Z**



**SRA160Z +
SRA158Z**




**SRA160Z +
SRA159Z**



**SRA161Z +
SRA158Z**




Reinforced
iron bumper



SRA165Z
reinforced iron bumper

150
PZ

Reinforced
iron bumper



SRA167Z
with bolt support

150
PZ

Rubber bumper to rivet



SRA166
30x25 mm

100
PZ

Galvanized handle
with plate assembled



SRA157Z
Without holes, handle bent downward

150
PZ

Galvanized handle
with plate assembled



SRA157ZR
Without holes, handle bent upward

150
PZ

Iron bumper for welding



SRA163Z
Iron bumper

400
PZ

Iron bumpers and
rubber bumpers



EXTRA20
Iron bumper and rubber bumper
already assembled

400
PZ

Rubber bumper to rivet



SRA1661
29x12 mm

100
PZ

Galvanized handle
with plate assembled



SRA157ZE
With holes, handle bent downward

150
PZ

Galvanized handle
with plate assembled



SRA157ZER
With holes, handle bent upward

150
PZ



QSTT nut/bolt 10x20mm
for tube supports, plates
and fixing brackets



SRA254Z

QSTT nut/bolt 10x20mm

100
PZ

Compatible with **SRA196Z - SRA197Z**

SRA198Z - SRA199Z - SRA250Z

SRA259Z - SRA801Z - SRA810Z

SRA815Z - SRA816Z

Nut/bolt for fixing
handles



SRA301Z

QSTT Nut/bolt 6x15mm for ixing handles
with holes and final slot

500
PZ


fima



www.csfima.it



Hook for connecting
spring box

Th. 1,5



SRA175Z
of 40 mm

150
PCS

Hook for connecting
spring box

Th. 1,5



SRA176Z
of 50/60mm

150
PCS

SRA176ZG
of 50/60 mm, Big bending

150
PCS

Hook for connecting
spring box

Th. 1,5



SRA174ZE
of 50/60mm, outer wrapping

150
PCS

SRA174ZEG
of 50/60mm, outer wrapping big bending

150
PCS


Hook



SRA170Z
Hook

200
PCS

Fixing brackets with
6MA hole



SRA150Z
of 110 mm

20
KG

SRA151Z
of 150 mm

20
KG


SRA152Z
of 220 mm

20
KG

SRA153Z
of 270 mm

20
KG

Spina di
bloccaggio



SRA154Z
from 110 mm \varnothing 6 mm for spring holder box

500
PZ

U-bolt for
deadbolt



SRA172Z
from 20 mm - passage sizes 22 x 9,7 mm

500
PCS

SRA169Z
from 25 mm - passage sizes 26,6 x 6,5 mm

500
PCS

SRA171Z
from 20 mm - passage sizes 26,6 x 10 mm

500
PCS

SRA164Z
from 20 mm - passage sizes 29 x 7,1 mm

500
PCS

Bracket
anti-tear



SRA401Z
for convex element

SRA402Z
for flat element

Guide mouth R/L
50 mm depth

Th. 1,5mm



SRA244ZA
for 22mm guide

50
PCS

SRA244ZB
for 25 mm guide

50
PCS

SRA244ZC
for 28mm guide

50
PCS

SRA244ZD
for 30 mm guide

50
PCS

Guide mouth R/L
40 mm depth

Th. 1,5mm



SRA244ZG
for 22mm guide

50
PCS

SRA244ZH
for 25 mm guide

50
PCS

SRA244ZI
for 28mm guide

50
PCS

SRA244ZL
for 30 mm guide

50
PCS




Guide mouth R/L
30mm depth




SRA210Z For 22mm guide	80 PCS
SRA208Z For 25mm guide	80 PCS
SRA206Z For 28 mm guide	80 PCS
SRA204Z For 30mm guide	80 PCS

Small fixed side plate
depth 30mm



SRA190Z 230x270 mm for tube Ø 60 mm Ø 48 mm, thick. 15/10	20 PCS
--	-----------

Fixed side plate
depth 30mm



SRA184Z 230x330 mm For tube Ø 60 mm 48 mm, thick. 15/10	20 PCS
SRA189Z 230x330 mm For tube Ø 60 mm Ø 48 mm, thick. 18/10	20 PCS
SRA186Z 230x330 mm For tube Ø 76 mm, thick. 18/10	20 PCS

Flat side plate with
slots -depth 50mm



SRA251ZA 300x300 mm, thick. 25-30/10	20 PCS
SRA252Z 350x350 mm, thick. 25-30/10	20 PCS
SRA253Z 420x420 mm, thick. 25-30/10	20 PCS

Flat side plate with
central slots only
Depth 50mm



SRA251Z 300x300mm thick. 25-30/10	150 PCS
---	------------

Cambered side plate with
slots -depth 50mm



SRA195Z 350x350 mm, thick. 25-30/10	20 PCS
SRA195AZ 420x420 mm, thick. 25-30/10	20 PCS

Flat fixed side plate
depth 50mm



SRA261Z 350x350 mm For tube Ø 60 mm, thick. 25-30/10	10 PCS
SRA263Z 350x350 mm For tube Ø 76 mm, thick. 25-30/10	10 PCS
SRA264Z 420x420 mm For tube Ø 76 mm, thick. 25-30/10	6 PCS

Flat fixed side plate
without side slots
Depth 50mm



SRA260Z 300x300mm thick. 25-30/10 for tube Ø 60mm, thick. 25-30/10	14 PCS
---	-----------

Cambered fixed side plate
with slots depth 50mm



SRA242Z 350x350 mm For tube Ø 60 mm, thick. 25-30/10	10 PCS
SRA243Z 350x350 mm For tube Ø 76 mm, thick. 25-30/10	10 PCS
SRA247Z 420x420 mm For tube Ø 76 mm, thick. 25-30/10	6 PCS

Side plate and guide
mouth welded



EXTRA14 Application of diaphragm guide invitation by welding	100 PCS
---	------------

Support for side plate

Ø 42 - Ø 48 - Ø 60 - Ø 76 Th. 2,50 mm



SRA196Z for pipe Ø 42 mm	50 PZ
SRA197Z for pipe Ø 48 mm	50 PZ
SRA198Z for pipe Ø 60 mm	50 PZ
SRA199Z for pipe Ø 76 mm	40 PZ

Flat side plate for 101 mm tube support 50 mm depth



SRA805Z 420x420mm, thickness 30/10	10 PZ
SRA800Z 500x500mm, thickness 30/10	10 PZ
Compatible with SRA801Z - SRA802Z SRA810Z - SRA254Z	

Adjustable support

Th. 2,50 mm



SRA250Z for pipe Ø 48 mm - Ø 60 mm - Ø 76 mm	50 PZ
--	----------

Support for tube Ø 101mm



SRA801Z Support for tube thickness 30/10	10 PZ
Compatible with SRA800Z - SRA802Z SRA805Z - SRA810Z - SRA254Z	

Sliding support

Th. 2,50 mm



SRA177Z for pipe Ø 42 mm	50 PZ
SRA178Z for pipe Ø 48 mm	50 PZ
SRA179Z for pipe Ø 60 mm	50 PZ

Plate for tube support Ø 101mm



SRA802Z Plate for pipe support thickness 30/10	10 PZ
Compatible with SRA800Z - SRA801Z SRA805Z - SRA810Z - SRA254Z	

Universal plate



SRA259Z pipe Ø 48 mm - Ø 60 mm - Ø 76 mm
--

QSTT nut/bolt 10x20mm for tube supports, plates and fixing brackets



SRA254Z nut bolt QSTT 10x20mm	100 PZ
Compatible with SRA196Z - SRA197Z SRA198Z - SRA199Z - SRA250Z SRA259Z - SRA801Z - SRA810Z SRA815Z - SRA816Z	

Flat side plate for wall tube fixing bracket Ø48/60/76mm



SRA251ZS 300x300mm, thickness 25-30/10	10 PZ
SRA252ZS 350x350mm, thickness 25-30/10	10 PZ
SRA253ZS 420x420, thickness 25-30/10	10 PZ
Compatible with SRA815Z - SRA254Z	



Kit side plate fixing
bracket to the wall for Ø 101
mm tube ∅ 101mm



SRA810Z

<L> fixing bracket including fixing bracket
reinforcement, thickness 30/10.
Compatible with

10
PZ

SRA800Z - SRA802Z

SRA805Z - SRA801Z - SRA254Z

Side plate fixing
bracket to the
wall for ∅ 48/60/76mm



SRA815Z

<L> fixing bracket thickness 30/10
compatible with



10
PZ

SRA251ZS - SRA252ZS



Tested in our facility with an applied force of **800 Kg**

Internal footprint of the spring boxes



Watch the tutorial video



MALÍA™

Nylon connecting rod
for rolling shutters

TUB309N

300
PZ

Nylon connecting rod
for rolling shutters

Compatible with **TUB305N** - GALVANIZED TUBE
STAINLESS STEEL TUBE - ALUMINUM TUBE

Available in various colours



Choose roller shutters of any style, size or design.

Reversible and compatible with all types of materials.

- Silent
- Non-Deformable
- Resistant
- Self-Lubricating



HOLE DIAMETER to 18 mm



WHEELBASE Length to 120 mm

Accessories for roller shutters





TUB305N

300
PZ


Lateral nylon chain
For tubes Ø 18 mm
Wheelbase 120mm
Mounting pins included

Compatible with **TUB305N - TUB302Z**
TUB303N - TUB309N - GALVANIZED TUBE
STAINLESS STEEL TUBE - ALUMINUM TUBE



Lateral nylon chain.

Designed to improve roller shutters' performance, our lateral nylon chain is made to have more fluidity of movement along the guides and a quicker and easier assembly.




Excellent fit along side guides:

Our highly resistant and flexible material guarantees an excellent automatic fit in the side guides.




Quick installation:

Thanks to pressure inserted nails, installation is fast.




Optimal sliding fluidity:

The nylon chain guarantees smooth and silent movement along the side guides.



Universal Compatibility:

Adaptable to all types of roller shutters, wheelbase 120mm, with nylon and galvanized steel connecting rods.



Connecting rod
for Ø 18 mm tube



TUB302Z
Galvanized steel, wheelbase of 120 mm

350
pcs

Connecting rod
for Ø 18 mm tube



TUB302INOX
Stainless steel, wheelbase of 120 mm

350
pcs

Nylon Connecting rod
for Ø 18 mm tube




TUB309N
Nylon, wheelbase of 120 mm

300
pcs

Connecting rod for
Ø 18 mm tube

thickness 1,8mm




TUB325Z
Galvanized steel, wheelbase of 95 mm

150
pcs

Connecting rod for
Ø 14 mm tube


thickness 2,0mm



TUB312Z
Galvanized steel, wheelbase of 60 mm

300
pcs

Nylon Connecting rod
repairs for Ø 18 mm tube



TUB303N
InNylon, wheelbase of 120 mm nylon

30
pcs

Connecting hook for
Ø 18 mm tube



TUB306Z
Galvanized steel

400
pcs

TUB306ZG
Galvanized steel, big bending

400
pcs

Connecting hook for
Ø 18 mm tube



TUB306INOX
Stainless steel

400
pcs

Connecting hook for
Ø 14 mm tube



TUB319Z
Galvanized steel

600
pcs

Side chain for
Ø 18 mm tube



TUB304Z
Wheelbase of 120 mm

100
MT

TUB326Z
Wheelbase of 95 mm

80
MT



Preformed clip for two tubes



thick. 1,8mm

TUB210Z

galvanized steel

700
PZ

TUB210INOX

stainless steel

700
PZ

Clip for two tubes with edges



TUB211Z

Galvanized steel

700
PZ

Clip for three tubes with edges



TUB212Z

Galvanized steel

600
PZ

Clip for two tubes



thick. 1,8mm

TUB317Z

Galvanized steel

900
PZ

Clip for three tubes



thick. 1,8mm

TUB318Z

Galvanized steel

700
PZ


Nylon connecting rod for repairing tubular rolling shutters

bielletta


TUB303N

Nylon connecting rod for tubular rolling shutters repairs

30 pz



diameter 18mm




120mm
wheelbase

- Easy to install
- Excellent smoothness
- Included kit of Torx screws self-tapping



Push and Stop: a universal security device for roller shutters.

Our security device, named "Push & Stop," is a component designed to avoid accidental opening of the roller shutter when the lock is engaged. This revolutionary instrument is a modern and reliable security solution for anyone looking for advanced security without the traditional drawbacks.





Benefits:

- **Increased Security:** Eliminate risk of damage to the roller shutter when the lock is engaged.
No compromised security, no damage to the lock, curtain or gearmotors.
- **Avoid accidental opening:** The Push & Stop allows you to use the lock safely without risking accidental opening.
- **Quick Installation:** The reduced size and intuitive design guarantee a simple installation.
- **Universal Compatibility:** Adaptable to all types of roller shutters, new or previously installed, for effective protection.

Push & Stop Button
with cable included



MDE10000
Nylon button with cable included

Fastening bracket
predisposition



MDE10005
Fastening bracket with side guide for
Push & Stop button


Plastic covering



MDE10010
Plastic covering

Push & Stop Smart Kit includes:

- Fastening bracket for
Push & Stop predisposition
- Push & Stop button with cable



MDE10020
Push & Stop Smart Kit

Push & Stop Pro Kit includes:

- Fastening bracket for
Push & Stop capability
- Push & Stop button with cable
- Plastic covering




MDE10030
Push & Stop Pro Kit

Compatibility:

Our Push & Stop device is compatible with all control panels equipped with a "Stop" function and with all low voltage control panels.

Interlocking gasket with glue inserted inside,
for "U" rail 1.50mm thick

- Noise reduction
- Reduction of friction
- Edge coverage to the guide
- High corrosion resistance
- Improved aesthetic appearance of the damper
- Versatile
- Quick and easy to apply
- Glue resistant to low and high temperatures
- Small packaging size (190x270mm)



Easy to install...
Customers always
satisfied.



Gaskets for side guide



SRA1471

Interlocking gasket

150
MT



SRA1475

4x7mm interlocking edge cover with Hot-Melt glue already inserted

200
MT



SRA1470

Gasket to rivet, L = 5000mm

150
MT




Compatible
with cod.
90P16

SRA1474

Interlocking gasket

200
MT



SRA1476

EPDM 14x27mm with internal iron reinforcement

Stop gasket for end element applicable to both the Italy and France models

- EPDM material
- Sponge end element
- Adheres perfectly to floor imperfections
- Reinforcing metal core
- Noise attenuation
- Resistant to sun and temperature changes
- Ductile, easy to apply and shape
- Small packaging size (55x55xh.19cm - Kg20)



Excellent in all situations. Adheres perfectly

Gaskets for final slat



SRA1472

Gasket for end element Mod. «Italia»

50 MT



SRA1473

Gasket for end element Mod. «Francia»

50 MT



SRA1476

EPDM 14x27mm with iron reinforcement

75 MT




SRA1476

EPDM 14x27mm with iron reinforcement

Side guides, profiles and tubes


Side guide with gasket housing



90P16
size 50x60, thickness 1,50mm

500 KG

Guide model "U"



90P05
In sizes H x L, th. 15-20/30

1000 KG

Guide model "□"

Thickness 1,50mm
Thickness 2,00mm




90P12
A: 50 mm, B: 73 mm

1000 KG

90P15
A: 80 mm, B: 73 mm

1000 KG

"L" profile for end slat Italy model



90P10
45x30 mm, thick 25-30/10

500 KG

90P11
50x30 mm, thick 25-30/10

500 KG

Guide to "G"



90P13
80 mm depth

Galvanized pipe for curtain roller shutter



TUB400Z
In galvanized steel ø 14 mm

5000 KG

TUB402Z
In galvanized steel ø 18 mm

5000 KG

TUB402INOX
In stainless steel ø 18 mm

5000 KG

Pipe Ø 14 wavy



TUB401Z
Ø 14 mm undulated tube

Tube for roller shutter



90TUBO42
In galvanized steel ø 42 mm

1000 KG

90TUBO48
In galvanized steel ø 48 mm

1000 KG

90TUBO60
In galvanized steel ø 60 mm

1000 KG

Tube for roller shutter



90TUBO76
In galvanized steel ø 76 mm

1000 KG

90TUBO101
In galvanized steel ø 101 mm

1000 KG

90TUBO133
In galvanized steel ø 133 mm

1000 KG



Nylon sliding blocks

For plane slat with interlocking



FRP004

With spline for french slat type, pitch 105 mm

500
PCS

For small plane slat



FRP005

For plane slat, pitch 70 mm

800
PCS

For insulated slat



FRP003

For double-wall insulated slat, pitch 115 mm

500
PCS

Element insulated



FRP006

For double-wall insulated profile, pitch 95 mm

800
PCS

For domed element



FRP001

For domed slat pitch 100mm

400
PCS

For plane slat



FRP002

For plane slat, pitch 115 mm

400
PCS

Encased handle



VER451Z

Encased handle

100
PCS

Hinge with holes



VER461Z

Without wheel

300
PCS

Hinge with holes



VER455Z

With iron wheel

300
PCS

Hinge with holes



VER459Z

With nylon wheel

300
PCS

End hinge R/L



VER467Z

With hole and iron wheel

200
PCS

End hinge R/L



VER475Z

With hole and nylon wheel

200
PCS

Hinge without holes



VER453Z

With iron wheel

300
PCS

Hinge without holes



VER457Z

With nylon wheel

300
PCS

End hinge R/L



VER463Z

Without hole, with iron wheel

200
PCS

End hinge R/L



VER471Z

Without hole, with nylon wheel

200
PCS



Upper support



VER483Z

Standard

50
PCS

Lower support



VER481Z

Large

50
PCS

Upper band guide



VER515Z

Size 35x35x35 mm

50
PCS

Plane iron sliding block



VER491Z

With iron wheels, pitch 110 mm

100
PCS

VER489Z

With iron wheels, pitch 115 mm

100
PCS

VER487Z

With iron wheels, pitch 120 mm

100
PCS

Plane iron sliding block



VER503Z

With nylon wheels, pitch 110 mm

100
PCS

VER501Z

With nylon wheels, pitch 115 mm

100
PCS

VER499Z

With nylon wheels, pitch 120 mm

100
PCS

Upper support



VER485Z

Large

50
PCS

Lower support



VER479Z

With spline

50
PCS

Lower band guide



VER517Z

Size 35x35x35 mm

50
PCS

Central lock



10C

Central lock, 3 keys included

10CKA

Central lock with same encryption, 3 keys included

Double bit side lock bent bolts



40DMLZ

Right and left, 3 keys included.

Side lock bent bolts



10ALZ

Right and left, 3 keys included.

10ALZKA

Right and left with same encryption, 3 keys included.

Double bit central lock



40DMC

Double bit central lock, 3 keys included

40DMCKA

Double bit central lock same encryption
3 keys included

Padlock



10LC

Padlock

Aluminium lock cover with central hole



10ACFM

5 MA threaded holes, handle included

50
PZ

Aluminium lock cover without central hole



10ASF

5 MA threaded holes, handle included

50
PZ

Fixing bolt



10A1

5 MA threaded holes for fixing lock

500
PZ

Fixing plate



40DM2

For double bit locks, threaded holes 5 MA

500
PZ

Nut and bolt for fixing lock



10A7

Bolts QSTT 6x25 mm for fixing lock

500
PZ

Fixing plate



10A3

With 5 MA threaded holes

50
PZ

Screw for fixing bolts



10A2


5X13 mm ts

500
PZ

Accessories for extendible gates



Diagonal with 5 holes



CES356Z

Size 510x15x2,5 mm


25
KG

CES360Z

Size 510x15x4,0 mm

25
KG

Diagonal with 5 holes




CES432Z

Size 400x15x2,5 mm

25
KG

Diagonal with 3 holes



CES364Z

Size 265x15x2,5 mm


25
KG

CES368Z

Size 265x15x4,0 mm

25
KG

Diagonal with 3 holes



CES434Z

Size 210x15x2,5 mm

25
KG

Long rivet



CES372Z	2700 PCS
5x47 mm tt	
CES374Z	2200 PCS
5x57 mm tt	

Short rivet



CES376Z	5000 PCS
4,8x10 mm tt	
CES378Z	5000 PCS
4,8x12 mm tt	

Small support



CES400Z	500 PCS
Of 40 mm	

Spacer tube



CES408Z	2500 PCS
Of 40 mm without edge	

Short nylon tube



CES427	5000 PCS
12x14 mm	
CES413	5000 PCS
12x17 mm	
CES414	5000 PCS
12x22 mm	

Spacer tube



CES404Z	2500 PCS
Of 40 mm with edge	

Short iron tube



CES412Z	2500 PCS
10x17 mm	

Sliding support



CES380Z	200 PCS
With iron wheels, ø 32 mm	

Sliding support



CES388Z	150 PCS
With nylon wheels, ø 33mm	

Single hinge



CES420Z	300 PCS
For overturning guide	



Hinge with stop



CES422Z
For overturnig guide

150
PZ

Hook for lock



CES424Z
Type "C"

500
PZ

Small plate




Thickness 2.0mm

CES430Z
40x25 mm with punched hole

1000
PZ

Galvanized "U" profile




90P01
15x15x15 mm, th. 1,2 mm

1000
KG

90P02
20x15x20 mm, th. 1,5 mm

1000
KG

Profile beat



Thickness 1.5mm

90P03
Galvanized profile beat in size 25x31x42 mm

1000
KG

Lock



20CF
Lock for folding gate
with milled cylinder 18,5 mm - 24 mm, 3 keys included

20CFKA
Lock for folding gate same encryption
with milled cylinder 18,5 mm - 24 mm, 3 keys included

Small plate



Thickness 3.0mm

CES433Z
With two 6 MA threaded holes

500
PZ

Small plate




Thickness 2.0mm

CES426Z
40x25, 6 MA threaded hole

1000
PZ

Galvanized profile "C"




Thickness 2.0mm

90P04
15x40x45x40x15 mm for upper guide

1000
KG

Galvanized "U" profile



Thickness 1.5mm

90P06
30x50x30 mm for lower guide

1000
KG

Turned device



CES317Z
Turned stopping device

100
PZ

Small plate



Thickness 3.0mm

CES431Z
With slot

500
PZ



Via Bonsarto 21, 50025 Montespertoli (Florence) Italy - info@csfima.it **Tel.** +39 0571.671614 **Fax.** +39 0571.601104 **PEC:** csfima@pec.it